

IN THE CLAIMS:

Please amend Claims 1 and 46, as follows. Note that all claims in the application are being reproduced below in accordance with current U.S. Patent and Trademark Office requirements.

1. (Currently Amended) An image forming apparatus comprising:

image bearing means for bearing a toner image;

an intermediary transfer member, wherein the toner image is electrostatically

transferred from said image bearing means onto said intermediary transfer member, and then

transferred from said intermediary transfer member onto a transfer material;

wherein said intermediary transfer member includes a first layer, a second layer on said first layer[[,]] and a third layer on said second layer, ~~for receiving~~ wherein said third layer receives the toner image from said image bearing means, and

wherein a volume resistivity of said first layer is smaller than that of said third layer, a volume resistivity of said third layer is smaller than that of said second layer, and wherein the volume resistivity of said third layer is 10^{10} to 10^{14} Ohm.cm.

2. (Previously Amended) An apparatus according to Claim 1, wherein the volume resistivity of said second layer is 10^{11} to 10^{15} Ohm.cm.

Claim 3 and 4 were previously cancelled.

5. (Previously Amended) An apparatus according to any one of Claims 1 and 2 , wherein said third layer has a thickness of 1-5 microns.

6. (Previously Amended) An apparatus according to Claim 5, wherein said second layer has a thickness larger than that of said third layer.

E' could
7. (Original) An apparatus according to Claim 5, wherein a plurality of the toner images are transferred onto said intermediary member so that an overlaid toner image is formed thereon, and the overlaid images are transferred from said intermediary transfer member onto the transfer material.

8. (Original) An apparatus according to Claim 7, wherein said image bearing means is provided with an image bearing member capable of bearing different color toner images.

9. (Original) An apparatus according to Claim 7, wherein said image bearing means is provided with a plurality of image bearing members for bearing different color images, respectively.

10. (Original) An apparatus according to Claim 5, further comprising transfer means for electrostatically transferring the toner image from said image bearing means onto said intermediary transfer member, wherein said transfer means applied a voltage to such a

side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

11. (Original) An apparatus according to Claim 10, wherein the voltage has a polarity opposite from a regular charging polarity of the toner.

12. (Original) An apparatus according to Claim 11, wherein said transfer means is provided with a voltage source for supplying the voltage.

13. (Original) An apparatus according to Claim 12, wherein said transfer means is provided with a roller contactable to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

14. (Original) An apparatus according to Claim 1 or 11, further comprising charging means for charging a surface of said image bearing means to a polarity which is the same as a regular charging polarity of the toner.

16. (Previously Amended) An apparatus according to Claim 1, wherein said first layer is elastic.

17. (Previously Amended) An apparatus according to Claim 16, wherein said first layer is a rubber layer.

18. (Original) An apparatus according to Claim 1, further comprising transfer means for electrostatically transferring the toner image from said image bearing means onto said intermediary transfer member, wherein said transfer means applied a voltage to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

19. (Original) An apparatus according to Claim 18, wherein the voltage has a polarity opposite from a regular charging polarity of the toner.

20. (Original) An apparatus according to Claim 19, wherein said transfer means is provided with a voltage source for supplying the voltage.

21. (Original) An apparatus according to Claim 20, wherein said transfer means is provided with a roller contactable to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

22. (Original) An apparatus according to Claim 1 or 19, further comprising charging means for charging a surface of said image bearing means to a polarity which is the same as a regular charging polarity of the toner.

23. (Original) An apparatus according to Claim 1, wherein said intermediary transfer member is in the form of a belt.

24. (Original) An apparatus according to Claim 23, further comprising supporting means for supporting said intermediary transfer member.

E' Cord
25. (Original) An apparatus according to Claim 24, wherein said supporting means is provided with a plurality of rollers.

26. (Original) An apparatus according to Claim 1, wherein a plurality of the toner images are transferred onto said intermediary transfer member so that an overlaid toner image is formed thereon, and the overlaid images are transferred from said intermediary transfer member onto the transfer material.

27. (Previously Amended) An apparatus according to Claim 26, wherein said image bearing means is provided with an image bearing member capable of bearing different color toner images.

28. (Previously Amended) An apparatus according to Claim 26, wherein said image bearing means is provided with a plurality of image bearing members for bearing different color toner images, respectively.

29. (Previously Amended) An intermediary transfer member onto which a toner image is electrostatically transferred from image bearing means, wherein the toner image

on said intermediary transfer member is transferred onto a transfer material, said intermediary transfer member comprising:

a first layer;

a second layer, provided on said first layer; and

a third layer, provided on said second layer, for receiving the toner image from

the image bearing means,

wherein a volume resistivity of said first layer is smaller than that of said third layer, a volume resistivity of said third layer is smaller than that of said second layer, and the volume resistivity of said third layer is 10^{10} to 10^{14} Ohm.cm.

30. (Previously Amended) An intermediary transfer member according to Claim 29, wherein the volume resistivity of said second layer is 10^{11} to 10^{15} Ohm.cm.

Claims 31 and 32 were previously cancelled.

33. (Previously Amended) An intermediary transfer member according to any one of Claims 29 and 30, wherein said third layer has a thickness of 1-5 microns.

34. (Previously Amended) An intermediary transfer member according to Claim 33, wherein said second layer has a thickness larger than that of said third layer.

35. (Previously Amended) An intermediary transfer member according to Claim 33, wherein a plurality of the toner images are transferred onto said intermediary transfer member so that an overlaid toner image is formed thereon, wherein overlaid toner images are transferred onto the transfer material and said intermediate transfer member.

E!
Cont'd

36. (Original) An intermediary transfer member according to Claim 29, wherein said intermediary transfer member is in the form of a belt.

37. (Original) An apparatus according to Claim 1, further comprising transfer means for applying a voltage to said first layer to electrostatically transfer the toner image to said intermediary transfer member from said image bearing member.

38. (Original) An apparatus according to Claim 1, wherein said first layer is coated with said second layer.

39. (Original) An apparatus according to Claim 1, wherein said second layer is coated with said third layer.

40. (Original) An apparatus according to Claim 1, wherein said first layer is coated with said second layer, and said second layer is coated with said third layer.

41. (Original) An apparatus according to Claim 1, wherein said first layer is an elastic layer.

E' Cond
42. (Original) An apparatus according to Claim 41, wherein said first layer is a rubber layer.

43. (Original) An apparatus according to Claim 29, wherein said first layer is coated with said second layer.

44. (Original) An apparatus according to Claim 29, wherein said second layer is coated with said third layer.

45. (Original) An apparatus according to Claim 29, wherein said first layer is coated with said second layer, and said second layer is coated with said third layer.

46. (Currently Amended) An image forming apparatus comprising:
image bearing means for bearing a toner image;
an intermediary transfer member, wherein the toner image is electrostatically transferred from said image bearing means onto said intermediary transfer member, and then transferred from said intermediary transfer member onto a transfer material,
wherein said intermediary transfer member includes a first layer and a second layer, wherein said second layer receives ~~for receiving~~ the toner image from said image bearing

means, wherein said first layer is integrally coated with said second layer, wherein said second layer has a volume resistivity smaller than that of said first layer, and the volume resistivity of said second layer is 10^{10} to 10^{14} Ohm.cm.

E!
Cont'd

47. (Original) An apparatus according to Claim 46, wherein the volume resistivity of said first layer is 10^{11} to 10^{15} Ohm.cm.

Claim 48 and 49 were previously cancelled.

50. (Previously Amended) An apparatus according to any one of Claims 46 and 47, wherein said second layer has a thickness of 1-5 microns.

51. (Original) An apparatus according to Claim 50, wherein said first layer has a thickness larger than that of said second layer.

52. (Original) An apparatus according to Claim 50, wherein a plurality of the toner images are transferred onto said intermediary transfer member so that an overlaid toner image is formed thereon, and the overlaid images are transferred from said intermediary transfer member onto the transfer material.

53. (Original) An apparatus according to Claim 52, wherein said image bearing means is provided with an image bearing member capable of bearing different color toner images.

E' cont'd

54. (Original) An apparatus according to Claim 52, wherein said image bearing means is provided with a plurality of image bearing members for bearing different color toner images, respectively.

55. (Original) An apparatus according to Claim 50, further comprising transfer means for electrostatically transferring the toner image from said image bearing means onto said intermediary transfer member, wherein said transfer means applied a voltage to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

56. (Original) An apparatus according to Claim 55, wherein the voltage has a polarity opposite from a regular charging polarity of the toner.

57. (Original) An apparatus according to Claim 56, wherein said transfer means is provided with a voltage source for supplying the voltage.

58. (Original) An apparatus according to Claim 57, wherein said transfer means is provided with a roller contactable to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

E1 Cont'd
59. (Original) An apparatus according to Claims 46, further comprising charging means for charging a surface of said image bearing means to a polarity which is the same as a regular charging polarity of the toner.

60. (Original) An apparatus according to Claim 46, wherein said intermediary transfer member is provided with a base layer, and wherein said first layer is provided on said base layer.

61. (Original) An apparatus according to Claim 60, wherein said base layer is elastic.

62. (Original) An apparatus according to Claim 61, wherein said base layer is a rubber layer.

63. (Original) An apparatus according to Claim 46, further comprising transfer means for electrostatically transferring the toner image from said image bearing means onto said intermediary transfer member, wherein said transfer means applied a voltage to such a

side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

E' *Con'd*
64. (Original) An apparatus according to Claim 63, wherein the voltage has a polarity opposite from a regular charging polarity of the toner.

65. (Original) An apparatus according to Claim 64, wherein said transfer means is provided with a voltage source for supplying the voltage.

66. (Original) An apparatus according to Claim 65, wherein said transfer means is provided with a roller contactable to such a side of said intermediary transfer member as is opposite from a side thereof for receiving the toner image.

67. (Original) An apparatus according to Claim 46 or 64, further comprising charging means for charging a surface of said image bearing means to a polarity which is the same as a regular charging polarity of the toner.

68. (Original) An apparatus according to Claim 46, wherein said intermediary transfer member is in the form of a belt.

69. (Original) An apparatus according to Claim 68, further comprising supporting means for supporting said intermediary transfer member.

70. (Original) An apparatus according to Claim 69, wherein said supporting means is provided with a plurality of rollers.

E!
Cont'd

71. (Original) An apparatus according to Claim 46, wherein a plurality of the toner images are transferred onto said intermediary transfer member so that an overlaid toner image is formed thereon, and the overlaid images are transferred from said intermediary transfer member onto the transfer material.

72. (Original) An apparatus according to Claim 71, wherein said image bearing means is provided with an image bearing member capable of bearing different color toner images.

73. (Original) An apparatus according to Claim 71, wherein said image bearing means is provided with a plurality of image bearing members for bearing different color toner images, respectively.

74. (Previously Amended) An intermediary transfer member onto which a toner image is electrostatically transferred from image bearing means, wherein the toner image on said intermediary transfer member is transferred onto a transfer material, said intermediary transfer member comprising:

a first layer; and

E1
cond
a second layer for receiving the toner image from said image bearing means,
wherein said first layer is integrally coated with said second layer, wherein said second layer has
a volume resistivity smaller than that of said first layer, and the volume resistivity of said second
layer is 10^{10} to 10^{14} Ohm.cm.

75. (Original) An intermediary transfer member according to Claim 74,
wherein the volume resistivity of said first layer is 10^{11} to 10^{15} Ohm.cm.

Claims 76 and 77 were previously cancelled.

78. (Previously Amended) An intermediary transfer member according to
any one of Claims 74 and 75, wherein said second layer has a thickness of 1-5 microns.

79. (Original) An intermediary transfer member according to Claim 78,
wherein said first layer has a thickness larger than that of said second layer.

80. (Original) An intermediary transfer member according to Claim 78,
wherein a plurality of the toner images are transferred onto said intermediary transfer member so
that an overlaid toner image is formed thereon, wherein overlaid toner images are transferred
onto the transfer material and said intermediate transfer member.

E1
end

81. (Original) An intermediary transfer member according to Claim 74, wherein said intermediary transfer member is in the form of a belt.

82. (Original) An apparatus according to Claim 74, wherein said intermediary transfer member is provided with a base layer, and said base layer is coated with said first layer.

83. (Original) An apparatus according to Claim 82, wherein said base layer is an elastic layer.

84. (Original) An apparatus according to claim 83, wherein said base layer is a rubber layer.
